

INTERMEDIATE BULK CONTAINER FOR OFFSHORE OPERATIONS

TOTE TANK 550 GAL (2,082 LITRES)

Salient Features:

- Patented one-piece sloped bottom assures uniform & complete drainage
- 1/4" thick combination lifting lugs for offshore & domestic applications
- 10 gauge stainless steel IBC construction with 2B finish
- 566 mm diameter top fill opening with removable drum cover
- Pressure relieving and venting device
- EPDM gasket with plated clamp ring
- Stackable up to four IBC containers high
- Patented one-piece stamped valve guard
- 2" top bung opening
- 304 stainless steel construction with 2" stainless steel ball valve
- Tank mounted operating instructions and warning labels

Dimensions & Weights

Length	: 1,067 mm
Width	: 1,219 mm
Height	: 1,905 mm
Tare Weight	: 295 Kgs
MPL	: 3,955 kgs
MGW	: 4,250. Kgs



DNV 2.7-1 Certified IBC transport frame is available for Offshore Operation. The Transportation Frame has passed extensive design and performance testing for strength, durability, and safety and meets all requirements of DNV 2.7-1 for offshore applications

Certificates & Standards



Tank Top



2" Bung Fitting in Tank Top



1/4" Thick Lifting Lug/Leg



Heavy Duty Tank Legs



Our rental programs offer includes :

- Rentals for both short-term and long-term periods.
- Daily, monthly and annual rentals with flexible rental terms.
- Fast mobilization and demobilization services.
- Services to our clients' facilities located across Southeast Asia region.